

Notes:

- 1. All dimensions in millimetres unless shown otherwise.
- All signs to comply with the Traffic Signs Regulations and General Directions 2016 (TSRGD 2016), BS 8442 & BS EN 12899-1 unless otherwise specified.
- 3. Posts shall not protrude above the top of the sign.
- Clearance to the edge of signs must be increased where there is a severe camber or crossfall or sign is in a central reservation.
- Signs erected on a single post shall be positioned so that the post is in the centre of the sign unless otherwise stated.
- Signs with a total area greater than 0.3m2 shall not be fitted to lamp columns except with the approval of OxonCC.
- Posts shall be tubular hollow steel and shall be protected from corrosion by hot dip galvanizing or grey painted, as directed by OxonCC.
- Min 100 thick surfacing to match existing in footways, min 150 deep topsoil in verges for galvanised posts, and 100 wide concrete collar for painted posts.
- All signs must be identified by a unique number and in a manner which will be approved by OxonCC.
- 10. In Oxford city, sign posts to be black painted or stainless steel.
- 11. Refer to OCC Street Lighting detail (to be updated)
- For further information refer to Standard Details Guidance Note drawing no. HSD/100/001

DRN CHCK'D DATE

BASE SIZES

POST SIZE	LENGTH	WIDTH	DEPTH	TYPE
76 ø	350	350	600	Α
89 ø	450	450	750	В
114 ø	600	600	800	С
140 ø	750	600	900	D
168 ø	900	700	900	Е
193 ø	900	750	1050	F

DRAWING TITLE: Series 1200: Traffic Signs - Non-Illuminated Traffic Signs REV **AMENDMENTS** DRAWING NO: OXFORDSHIRE COUNTY COUNCIL DRAWN SCALE: NTS CHECKED HSD/1200/005 INITIALS: CS MS DATE: 12/01/2024 12/01/2024 © 2020 Oxfordshire County Council