

Notes:

- 1. All dimensions are in millimetres unless shown otherwise.
- 2. Post & rail fence shall be to B.S.1722 Part 7. Type SPR13/4 with rails fixed to the private property side.
- Barbed wire shall be conventional zinc coated with barbs at 75mm spacing and comply with BS EN 10223-1.
- Badger netting shall be steel wire welded mesh to BS EN 10223-4 with zinc/zinc alloy wire with black organic coating 100x100 mesh size and 2.5mm diameter.
- 5. Barbed wire shall not be used adjacent to footways/footpaths.
- 6. Rails to be connected to the posts on the opposite side to the carriageway.
- The fence to comply with MHCW Volume 2 SERIES NG 300 FENCING CL304/305.1/311 for timber quality and sustainability, fixing quality and timber treatment.
- 8. The wooden post and rail fences shall comply with BS1722 Part 7.
- 9. For further information refer to Standard Details Guidance Note drawing no. HSD/100/001
- For concrete specifications and mix information refer to the Concrete For Ancillary Purposes Standard Specification drawing no. HSD/100/002.

WOODEN POST & FOUR RAIL WITH BADGER NETTING & BARBED WIRE

	DRAWING TITLE:								
	Series 300: Fencing - Pe	Series 300: Fencing - Permanent Fencing Type 2 - with Badger Netting							
						AMENDMENTS	DRN	CHCK'D	DATE
OXFORDSHIRE COUNTY COUNCIL	SCALE: NTS		DRAWN	CHECKED	DRAWING NO: HSD/300/015				
		INITIALS:	CS	MS					
© 2020 Oxfordshire County Council.		DATE:	12/01/2024	12/01/2024					