

PEDESTRIAN/BRIDLE TIMBER FIELD GATE

Notes:

- All dimensions are in millimetres unless shown otherwise.
- 2. All gates shall open away from the highway.
- For details of fittings for hanging and fastening see MHCW Highway Construction Details Drawings No. H30, H31 and H32.
- 4. For gates on PRoW, post footing material to be in accordance with BS.5709:2018.
- 5. Minimum width of pedestrian gate = 1100mm.
- All gate types to have latches that are easy to use, bridle gates to have latches that can be operated from horseback.
- 7. Gate and all associated supports and fixings are to comply with BS.1722.
- 8. For further information refer to Standard Details Guidance Note drawing no. HSD/100/001
- For concrete specifications and mix information refer to the Concrete For Ancillary Purposes Standard Specification drawing no. HSD/100/002.

Top rail	100x75 tapering to 75x75 75x25 75x25 100x75 75x75					
Under rails						
Braces						
Hanging stile						
Shutting stile						
Shutting post	2100x175x175					
Hanging posts	2100x200x200					

DIMENSIONS OF TIMBER MEMBERS

Series 300: Fencing - Pedestrian/Bridle Gate									
					REV	AMENDMENTS	DRN	CHCK'D	DATE
OXFORDSHIRE COUNTY COUNCIL	SCALE: NTS		DRAWN	CHECKED	DRAWING NO:				
COUNTY COUNCIL		INITIALS:	cs	MS					
© 2022 Oxfordshire County Council.		DATE:	12/01/2024	12/01/2024					