## - Edge of carriageway 450 200 Varies - ideally 1100 to 1950 (to avoid wheel tracks) 300 Verge backfilled Existing construction -45° Bond coat to horizontal and vertical surfaces 250 type 1 sub-base 40mm HRA 35/14 surf 40/60 PEN des. with 20mm pre-coated chippings to clause 911 SHW or AC 10 Close Surf 100/150 (Min PSV 65) 60 binder course AC20 dense bin 70/100 150 base AC32 HDM base 40/60 Sub-grade

## Notes:

- 1. All dimensions are in millimetres unless shown otherwise.
- Construction specification and depths for classified roads to be submitted and approved by OxonCC.
- For further information refer to Standard Details Guidance Note drawing no. HSD/100/001

## EDGE STRENGTHENING TYPICAL CROSS-SECTION FOR UNCLASSIFIED ROADS

	DRAWING TITLE:								
	Series 700: Road Pavements General - Edge Strengthening								
					REV	AMENDMENTS	DRN	CHCK'D	DATE
OXFORDSHIRE COUNTY COUNCIL	SCALE: NTS		DRAWN	CHECKED	DRA	WING NO:			
		INITIALS:	cs	MS		HSD/700/200			
© 2020 Oxfordshire County Council.		DATE:	12/01/2024	12/01/2024					